


## IceniCAM Information Service



## SPECIAL FITTING FEATURES



Special extension nut is provided for fitting rear wheel. Speed gear is



The belt wheel fits to the spokes of bicycle rear wheel, giving even thrust, reducing general strain.






Illustration shows adjustable bracket to suit all standard cycle frames.








Decompressor for easy starting.

It is simplicity itself to fit the "Cyclaid" to your bicycle - and how pleased you'll be with the results! Easy going all the way, it's a pleasure to ride to work and there's no work on your pleasure trips! Go to your nearest "Cyclaid" agent and see it demonstrated for yourself.

> KING & HARPER LTD. MOTOR CYCLE DEPT. MILTON ROAD CORNER CAMBRIDGE




## SPECIFICATION

Stroke 32 mm. Bore 35 mm. Piston displacement 3l c.cm. Compression ratio 1856. Aluminium cylinder with inserted metal liner. Cylinder Cylinder head Aluminium, detachable. Special rotating magnet with sparking plug. Advance ignition 2.6 mm. Carburettor Reduction ratio In motor 1:3.7 By belt drive 1:5. 1 : 18.5. Total reduction ratio Belt drive by endless rubber texture V belt. Power transmission Fuel tank Capacity about 3 pints. Normal oil-petrol two-stroke mixture. I part oil to 30 parts petrol. Fuel 0.7 H.P. at 3,500 R.P.M. Continuous output

Continuous speed

About 12 M.P.H. 18 20 M.P.H. 300 M.P.G. (approx.). Weight of the total in- 14/15 lb. complete with tank and all accessories.



Produced by Larder & Stevens Ltd., and printed on a SALMSON RANGER Press.

