

## TRICAMPEONA 3 E 49 c.c.





High performance 2-stroke engine built by Derbi 38 mm, bore 44 mm, stroke 48.7 G.C.
9:1 Compression ratio developing 4.5 H.P. 5700 R.P.M.
Newly designed cylinder and cylinder head heavily finned for improved cooling.
Dell'Orto carburettor type SHA 14-14 fitted with intake silencer drawing through inside of frame.
Ignition by Motoplat 6 volt. 18 watt.
Magnetic flywheel with shielded coil.
Primary drive by helical gears fitted with damper to ensure quiet operation.

ration.

ing type multiplate clutch running in oil bath.

ily polished aluminium crankcase covers.

t operated 3 or 4 speed gearbox with outside adjustment is starter.



+ 1/3 Gallon fuel tank, stove enamelled in high



Rear suspension by swinging fork and cushioned by double spring hydraulic shock absorbers. Very powerful 105 mm. diameter drum brakes front and rear. Large highly efficient chromed silencer.










in 1969-1970: 50 cc.; 1971-1972: 125 cc.

NACIONAL MOTOR, S. A.

CICLOMOTORES/MOTOCICLETAS MOLLET DEL VALLES - MARTORELLAS BARCELONA - ESPAÑA



## IceniCAM On-Line Library



www.icenicam.org.uk