# THE GILERA 50TS



How the Italians separate the men from the boys.



When you're ready for it, you'll know.



## **SPECIFICATION**

#### **ENGINE:**

2 stroke single cylinder. Lubrication: crankshaft by petrol oil mixture. Gearbox and clutch by oil thrower. Capacity: 49.77 cc. Bore: 38.4 mm. Stroke: 43 mm. Compression ratio: 10:1.

#### CLUTCH:

Wet type multiplate. Gearbox: 5 speed constant mesh. Ignition: flywheel magneto. Carburettor: Dell'Orto SHA.14/12.

#### FRAME:

Duplex cradle type. Front suspension: hydraulic forks. Rear suspension: swinging arm with hydraulic shock absorbers. Tyres: front – 2.50 x 17", rear – 2.75 x 17".

#### **DIMENSIONS:**

Dry weight: 82 Kg. (180.8 lbs. approx.) Max. length: 1900 mm. (74.8" approx.) Max. width: 730 mm. (28.74" approx.) Wheel base: 1225 mm. (48.22" approx.) Max. gradient: 40% (2.5:1)

#### **PERFORMANCE & CONSUMPTION:**

Fuel Tank capacity: 8.8 litres including 1 litre reserve. (1.94 galls. incl. .22 gall. reserve) of 4% (25:1) petroil mix.)
Fuel consumption: up to 105 mpg. (CUNA standards).

#### Your Gilera Dealer is:

FRAN RIDEWOOD & Co. BURCOTT BRIDGE MOTORCYCLES

WESTFIELD ROAD WELLS, SOMERSET BA5 2HS, TEL: 73462



### Douglas (SALES & SERVICE) LTD.

1/2 Oak Lane, Fishponds Trading Estate, BRISTOL BS5 7XB. Tel: Bristol (0272) 654197 and 654882

Note: The company reserve the right to introduce any modification to this specification without prior notice and therefore the information contained in this leaflet does not constitute any term of sale. All descriptions and figures are given in good faith and intended to apply generally. Variations in performance and construction on individual machines can occur according to prevailing circumstances and rider. All performance figures are to CUNA standards.



VESPA

GILERA

BIANCHI

## IceniCAM Information Service



www.icenicam.org.uk